



MOBILE HEATED CABINET

C9 shown with optional push handles, grey powder coat, and transport bumpers.

Heavy-duty heated
holding/transport cabinet for
use with **12" X 20" Pans**

MODELS

C5

C9

C12
UP

C16

Job: _____

Item No. _____



MOBILE HEATED CABINET



Armor Heat® System



Fully Insulated



Cabinet is fully framed all vertical and horizontal edges.



Caster Mounting Plates fully welded to cabinet framing



Caster Mounting Plates 6" X 6" X 5/16" steel plate drilled and tapped



All Hardware mounted through framing



Door Framed, Insulated, and Gasketed



Door Louvered with Adjustable Damper



Top-Mounted Control Panel



All Stainless Steel Construction



60 to 230 Degree Temperature Range



5" Casters Standard



Low Power Requirements



Pan Guides permanently mounted



Accommodates **12" X 20" Pans** in 2", 4", or 6" depth



Accommodates **1/2" and 1/3" Size Pans**





C5, C9, come complete with **Four Side-Lift Handles**



C5, C9, available with **Removable Dolly**

MODEL SPECIFICATIONS



MODEL #	CAPACITY 12" X 20" - 2 1/2" pans	WIDTH DIM A	DEPTH DIM B	HEIGHT DIM C	VOLTAGE	WATTAGE	AMPERAGE	SHIP WEIGHT
C5	5	19 1/2"	29"	35 5/16"	120	500	4.16	SS-160 Lbs.
C9	9	19 1/2"	29"	45 1/16"	120	500	4.16	SS-280 Lbs.
C12UP	12	19 1/2"	29"	54 3/16"	120	900	8.25	300 Lbs.
C16	16	19 1/2"	29"	65 13/16"	120	900	8.25	355 Lbs.



GENERAL

Cabinet shall be constructed throughout with stainless steel. All double-wall construction that is insulated with high-density fiberglass insulation. All exterior surfaces shall be ground and polished to a #4 finish.



INNER CABINET

Inner cabinets shall be all 24 gauge 300 series. Stainless steel inner cabinet shall have permanently mounted pan rails. Rails shall accommodate 12" X 20" X 2 1/2" pans or multiple 4" and 6" pans. Cabinet will also accommodate 1/2" and 1/3" pans. Inner cabinet is fully insulated with high-density fiberglass; 2" on sides and back and 4" on top and bottom. Inner cabinet is heated by the Armor Heat® system.



DOOR

Door shall be all 20 gauge stainless steel. Door shall have full interior frame constructed of 3/4" X 3/4" 14 gauge Galvanized angle steel. Door shall be fully insulated and gasketed. Door shall have an exterior louver with an interior damper for moisture control. All door hardware shall be secured through framing in cabinet and door. Door shall have a heavy-duty positive and magnetic door latch and heavy-duty refrigeration-type door hinges.



ELECTRICAL CHARACTERISTICS

Cabinets shall have a top-mounted control panel consisting of an on/off switch with power indicator light, and electronic control with digital temperature display. Each cabinet shall be heated by a 120 volt, 60 cycle, 1 phase heating system. Cabinets shall come complete with a permanently mounted 8' cord with a Nema #5-15P plug. Top of cabinet is removable for easy access to controls.



CASTERS

Cabinet shall have 4 heavy-duty 5" casters, 2 rigid and 2 swivel casters mounted to 6" X 6" X 5/16" steel plate that is drilled and tapped.



BASE

1/8" formed steel base with four 6" X 6" X 5/16" steel plates drilled and tapped to accommodate 5", 6" or 8" casters. The plates are fully welded to frame on all four sides.



INTERNAL FRAME

All vertical and horizontal edges framed with a combination of 1 1/2" X 1 1/2" X 1/8" angle steel, arc welded, cross braced, and reinforced at all corners.



ACCESSORIES, OPTIONS, VARIATIONS



Pass-thru Doors



Left-Hand Hinged Doors



Alternate Rail Spacing



Vertically-Mounted Push Handles



Choice of **Heavy-Duty Casters**, 5" X 2", 6", or 8"



Exterior Edges protected with 1" X 1" X 1/8" stainless steel angle



Flush-Mounted Heavy-Duty Paddle Latch



Heavy-Duty Transport Latch that will accept a padlock, 12 gauge stainless steel



Stainless Steel Perforated Shelves



Side Mount Gravity Latch



Dutch Doors



Cord Reel



Sterno Adapter



Lexan Door



Stainless Steel Adjustable Legs



Heavy-Duty Bumper System



Tamper Proof Fasteners



Control Panel Cover, lockable



Heavy-Duty Perimeter Bumper



Dolly with Casters for C5