





Designed to accommodate

18" X 26" or 14" X 18" Trays and

12" X 20" Pans

**MODEL** 





# SUPER HOLD CABINET



Armor Heat<sup>®</sup> System



**Fully Insulated** 



Stainless Steel Interior and Exterior



**Cabinet is Fully Framed** all vertical and horizontal edges



**Caster Mounting Plates** fully welded to cabinet base



**Caster Mounting Plates** 6" X 6" X 5/16" steel plate drilled and tapped



**All Hardware Mounted** through framing



Door Framed, Insulated and Gasketed



Door Louvered with Adjustable Damper



**Top Mounted Control Panel** 



60 to 230 Degree Temperature Range



**5**" Casters Standard



**Low Power Requirements** 



Two completely separate
Fully Insulated Inner Cabinets



Separate Controls and Heating Systems for each compartment



Universal Angles Adjustable on 1 1/2" centers accommodate 250 lbs per pair



**Universal Angles** will accommodate 2 (12" X 20") pans or 1 (18" X 26") tray



**Universal Angles Chrome-Plated** with heavy nickel and clear coat



Accommodates **5 Sets of Universal Angles** per compartment




**Universal Angle Posts** removable for cleaning


## **MODEL SPECIFICATIONS**















MODEL#	CAPACITY	WIDTH	DEPTH	HEIGHT	VOLTAGE	WATTAGE	AMPERAGE	SHIP
		DIM A	DIM B	DIM C				WEIGHT
SH14UA	10 sets - UA brackets	28 1/2"	38"	74 7/8"	120	1480	12.33	530 Lbs.



### **GENERAL**

Cabinet constructed with stainless steel, all double-wall construction. Insulated with high-density fiberglass insulation. All exterior surfaces shall be ground and polished to a #3 finish.



### **INNER CABINET**

Inner cabinet shall be all 24 gauge 300 series stainless steel. Inner cabinet shall have permanently mounted rails. Shall have universal angles constructed of heavy gauge wire, and vertical and horizontal, 11 gauge flat stock. Each pair shall accommodate 250 lbs. Universal angles are chromeplated with heavy nickel and a clear coat and adjustable on 1 1/2" centers. Holding posts removable for cleaning. Universal angles will accommodate 2 (12" X 20") pans per set, or 1 (18" X 26") tray, or 2 (14" X 18") trays. Inner cabinet fully insulated with highdensity fiberglass; 2" on sides, back, top and bottom. Cabinet shall have Armor Heat® System.



### **DOOR**

Door shall be all 20 gauge stainless steel. Door shall have full interior frame constructed of 3/4" X 3/4" 14 gauge Galvanized angle steel. Door shall be fully insulated and gasketed. Door shall have an exterior louver with an interior damper for moisture control. All door hardware shall be secured through framing in cabinet and door. Door shall have a heavy-duty positive and magnetic door latch and heavy-duty refrigerationtype door hinges.



### ELECTRICAL CHARACTERISTICS

Each cabinet shall have a top-mounted control panel consisting of an on/off switch with power indicator light, electronic temperature control with digital display. Each cabinet shall be heated by a 120 volt, 60 cycle, 1 phase heating system. Cabinets shall come complete with a permanently mounted 8' cord with a Nema #5-15P plug. Top of cabinet is removable for easy access to controls.



### **CASTERS**

Cabinet shall have 4 heavyduty 5" casters, 2 rigid and 2 swivel casters mounted to 6" X 6" X 5/16" steel plate drilled and tapped.



### **BASE FRAME**

1/8" formed steel base. Base shall have four 6" X 6" X 5/16", steel plates drilled and tapped to accommodate 5", 6", or 8" casters. The plates are fully welded to frame on all 4 sides.



### INTERNAL FRAME

All vertical and horizontal edges framed with a combination of 1 1/2" X 1 1/2" X 1/8" and 1" X 1 1/8" angle steel, arc welded, cross braced and reinforced at all corners.



## **ACCESSORIES, OPTIONS, VARIATIONS**



**Pass-thru Doors** 



**Side-Mount Gravity Latch** 



**Left-hand Hinged Doors** 



**Dutch Doors** 



Vertically Mounted Push Handles



**Cord Reel** 



Choice of Heavy-Duty Casters, 5" X 2", 6" and 8"



Sterno Adapter



Flush-Mounted Heavy-Duty Paddle Latch



**Lexan Doors** 



Stainless Steel Perforated Shelves



Stainless Steel Adjustable Legs



**Heavy-Duty Transport Latch** that will accept a padlock, 12 gauge stainless steel



**Perimeter Bumper Guards**